

## Optidrive E3 Datasheet

**Model:** ODE-3-120070-1F12

### Input Ratings

Supply Voltage	200-240V
Input Phases	1
Supply Current Continuous	12.9 Amps
Supply Fuse or MCB (Type B)	16 Amps

### Output Ratings

Motor Output Rating	2 HP
Output Voltage	0 – Supply Voltage
Output Current	7 Amps

### Cable Information

Max Supply Cable Size	8 mm <sup>2</sup>
Max Motor Cable Size	8 mm <sup>2</sup>
Max motor cable length	100 metres

### VFD Factory Build Options

<b>EMC Filter</b>	Internal EMC Filter
<b>Brake Transistor</b>	No Internal Brake Transistor
<b>Enclosure</b>	IP20

### Installation Options & Peripherals

- ▶ **Communication Interfaces**
- ▶ **EMC Filters**
- ▶ **I/O Options**
- ▶ **Input Chokes**
- ▶ **Optistick Smart**
- ▶ **Output Filters**
- ▶ **Remote Keypads**
- ▶ **RJ45 Accessories**
- ▶ **USB PC Connection Kit**



### Dimensions



Size	1
Height	173mm
Width	83mm
Depth	123mm
Weight	1Kg
Fixings	4 x M5